

SRL; Twin Turbo (704346-1)

Achieve 100% tie-off while reducing fall distance to inches.

Key Features:

- Preferred fall arrest system when performing mid air transfers, working over water or where dangling independent safety lines pose a hazard
- Requires less fall clearance because it arrests a fall within inches
- Replacement for Y-Lanyards
- Connects to the back D-ring of any fall protection harness
- Permits retractables to swivel in multiple directions for greater mobility
- Webbing pays out smoothly – extends/retracts without interruption
- Similar weight to standard Y-Lanyards



Part Number	End Connector	Weight
704346-1	ANSI Snap Hook	4.9 lb (2.2 kg)
704346-2	ANSI Rebar Hook	6.7 lb (3 kg)
704346-3	Snap Hook	4.7 lb (2.1 kg)
704346-4	Rebar Hook	6.1 lb (2.8 kg)
704346-5	Aluminum Snap Hook	4.2 lb (1.9 kg)
704346-6	Aluminum Rebar Hook	5.6 lb (2.5 kg)

Specifications:	704346-1
Webbing Tensile Strength:	Min. 5,000 lb (2,268 kg)
Working Length Capacity:	6 ft. (1.8 m)
Technical Max Worker Rating:	400 lb (181.4 kg)
Certification	Meets the following at time of shipment: ANSI: Z359.1-2007, A10.32 OSHA: 1926.502, 1910.66 CSA: Z259.12-01 Class 1, Z59.2.2-98

Rebar Assemblies

Chain and webbing

Work positioning connectors used in form work and rebar applications



BD-00015:

- 14 in. (356 mm) chain with adjusting link
- 2 double locking hooks
- 1 double locking form hook with swivel



701270-1:

- 13 in. (330 mm) web
- 2 double locking hooks
- 1 double locking form hook