



MKD2



Designed especially for narrow access situations, the MKD2 is used in boilers, digesters, vessels and all tight places. Unique modular, hinge and pin design allows the MKD2 components to easily fit through 18 in. (457 mm) openings.

- Lightweight, heavy duty aluminum
- Load up to a 40 ft (12.2 m) platform in a small truck
- Load ratings:
 - 5-30 ft (1.5-9.1 m): load rated at 1,000 lbs. (453.6 kg)
 - 35 or 40 ft (10.7 or 12.2 m): load rated at 750 lbs. (340.2 kg)
- Modular 5 or 10 ft (1.5 or 3 m) sections

Available in rental fleet only

INDUSTRIAL PRODUCT OFFERINGS

Specifications: Weight & Capacity

Length	Configuration	Total Weight
5 ft (1.5 m)	5	211 lbs. (95.7 kg)
10 ft (3 m)	10	306 lbs. (138.8 kg)
15 ft (4.6 m)	10 5	433 lbs. (196.4 kg)
20 ft (6.1 m)	10 10	510 lbs. (231.3 kg)
25 ft (7.6 m)	10 5 10	636 lbs. (288.5 kg)
30 ft (9.1 m)	10 10 10	713 lbs. (323.4 kg)
35 ft (10.7 m)	10 10 10 5	840 lbs. (381 kg)
40 ft (12.2 m)	5 10 10 10 5	966 lbs. (438.2 kg)

Also Available

Spider Part #	MKD2 Components
MKD011	2 1/2 ft (0.8 m) Floor
MKD012	2 1/2 ft (0.8 m) Side Panel
MKD013	2 1/2 ft (0.8 m) Top Rail (used as mid and top rails)

Frequently used accessories:

**Ground any platform with 701151-1
Safety Welding Ground on page 137.**

MKD2 Configurations

Length	End Stirrup MKD001	Connect Frame MKD006	Floor		Side Panel		Side Rail		Floor Pins MKD010	Wall Roller MKD009R
			10 ft (3 m) MKD003	5 ft (1.5 m) MKD002	10 ft (3 m) MKD008	5 ft (1.5 m) MKD007	10 ft (3 m) MKD005	5 ft (1.5 m) MKD004		
5 ft (1.5 m)	2	-	-	1	-	2	-	2	2	2
10 ft (3 m)	2	-	1	-	2	-	2	-	2	2
15 ft (4.6 m)	2	1	1	1	2	2	2	2	4	2
20 ft (6.1 m)	2	1	2	-	4	-	4	-	4	2
25 ft (7.6 m)	2	2	2	1	4	2	4	2	5	2
30 ft (9.1 m)	2	2	3	-	6	-	6	-	5	2
35 ft (10.7 m)	2	3	3	1	6	2	6	2	8	2
40 ft (12.2 m)	2	4	3	2	8	4	8	4	10	2

For more information, call: 1-877-774-3370