

Harnesses



The right harness should be as comfortable as your regular clothing. Strap on a Spider harness and you'll feel the difference. Pull the straps and it's instantly sized for your body.

Spider harness features:

- Lanyard loop eliminates slack and tripping hazards
- Sewn-in chest strap assures proper position
- No-slip SURE-GRIP web prevents loosening for constant fit
- Fastening options:
 - Adjustable mating buckle for fast hook-up and proper fit
 - Tongue buckle leg straps allow quick, secure adjustments
- Durable, removable tool belt (optional)
- 6 in. (152 mm) padded back support for maximum comfort and fatigue reduction (optional)
- Replaceable shoulder pads to distribute the weight of the tool belt (optional)
- Sub-pelvic strap gives greater support and keeps the user upright while arresting a fall
- Sliding back D-ring
- Quick to don and easy to adjust
- Sturdy hardware

Harness Sizing Chart

Harness Size	Waist Measurement
Small/Medium	29 – 36 in. (737 – 914 mm)
Large/X-Large	36 – 50 in. (914 – 1,270 mm)
<i>XXL available in select harnesses. Call Spider for details.</i>	

Belt Size	Waist Measurement
Small	32 – 41 in. (813 – 1,041 mm)
Medium	38 – 47 in. (965 – 1,194 mm)
Large	42 – 51 in. (1,067 – 1,295 mm)
X-Large	46 – 55 in. (1,168 – 1,397 mm)
XX-Large	49 – 58 in. (1,245 – 1,473 mm)

Harness Family	Side D-rings	Front D-ring	Retrieval Rings	Lanyard Loops	Waist Belt	Shoulder Pads	Back Pad	Stretch Material
Fall Arrest	No	No	No	1	No	No	No	No
Stretch Fall Arrest	No	No	No	1	No	Yes	No	Yes
Fall Arrest With Waist Belt	No	No	No	1	Yes	No	No	No
Constructor	Yes	No	No	1	Yes	Yes	Yes	No
Stretch Constructor	Yes	No	No	1	Yes	Yes	Yes	Yes
Constructor, double loop	Yes	No	No	2	Yes	Yes	Yes	No
Confined Space Entry	No	No	Yes	1	No	Yes	No	No
Positioning	Yes	No	No	1	No	No	No	No
Climbing	No	Yes	No	1	No	No	No	No

Technical Data – Full-Body Harnesses

Certification:	Fully complies with ANSI A10.14, 1991 and ANSI Z359.1, 1992 standards and all OSHA requirements, including 1910.66 Appendix C and 1926 Subpart M.
Description:	A full-body fall arrest harness offering lightweight webbing, leg adjustments, chest strap, back sliding D-ring for fall protection and semi-universal sizing
Identification:	Identification is made by a tag attached to the harness stating manufacturer, date of manufacture, model and serial number.
Material of Construction:	Webbing: 1 3/4 in. (44 mm) Nylon webbing D-rings: Stamped steel D-ring with minimum tensile strength of 5,000 lbs. (2,268 kg). The D-ring is cad or zinc plated and meets the ASTM fifty-hour salt spray test requirements. 100% proof tested
Load Limit:	1 Worker (310 lbs. [140.6 kg] – person, tools, etc.)
Weight:	3-6 lbs. (1.4-2.7 kg), depending on model
Warranty:	All Spider harnesses are warranted against any defects in workmanship and materials for a period of one year from the date of purchase when purchased in the United States. This warranty does not cover damage caused by accident, abuse, misuse or an act of God (such as a flood). Consequential and incidental damages, including without limitation, loss of property and those arising from breach of any express or implied warranty, are not the responsibility of Spider and, to the extent permitted by law, are excluded.

For more information, call: 1-877-774-3370