

# Corner Support Post (701877-1)

**Extends reach of current outrigger beams by moving fulcrum point forward into building corners.**

## Key Features:

- For use in building corner applications to shorten the reach needed from available beams
- For use with all 4x4 SA-1088, 6x4 and 5x5 8-0217-x series beams, 700809-1 & 700819-1 6 in. (152 mm) square tube beams
- Attaches to: OBSF Frame A-11393, Rolling Outrigger Gantries 701960-1 and 701960-2
- Enables the use of corner-mounted hoist in the 008812-1 Adjustable Corner Adapter to improve stability, load capacity, and load distribution on angle platforms
- Allows beam fulcrum point to be extended into corners and limited spaces where gantries and frames cannot reach
- Can be used with 2 stacked OBSF frames at maximum height
- Heavy duty steel construction
- Thorough labeling ensures worry-free installation
- Height completely adjustable from 5 ft. 5 in. (1.7 m) to 9 ft. 4 in. (2.8 m)
- Made by Spider in the USA

<b>Specifications:</b>	<b>701877-1</b>
<b>Load Rating:</b>	Up to 1,500 lb (680.4 kg)
<b>Weight:</b>	94 lb (42.6 kg) in 3 pieces, heaviest piece = 54 lb (24.5 kg)
<b>Outreach:</b>	see beam specifications



Standard Scaffold Clamp allows attachment to: OBSF Frame A-11393, 701960-1, 701960-2, and gantry frames.

