

Splice Tubes



700757-1*

Spider pioneered the 3 ft (0.9 m) splice tube and now makes a 9 ft (2.7 m) splice tube to replace cumbersome splice plates held in place with nuts and bolts. The time saving splice tubes can be used on 6 x 4 and 5 x 5 H or I beams.

Key Features:

- No tools needed for assembly
- Simple locking pin design makes connecting fast and easy.
- Saves 30 minutes of rigging installation time per swing stage
- Eliminates rework of misaligned bolt patterns
- Built by Spider in the USA



8-0217-3

Part Number	700757-1*	8-0217-3	8-0217-4
Length:	3 ft (0.9 m)	3 ft (0.9 m)	9 ft (2.7 m)
Weight:	13 lb (5.9 kg)	13 lb (5.9 kg)	39 lb (17.7 kg)
Construction:	Aluminum extrusion	Aluminum extrusion	Aluminum extrusion
Replaces Splice Plates on:	6 x 4 Beam Outriggers sold as SA-10841	5 x 5 Beam Outriggers sold by others	5 x 5 Beam Outriggers sold by others
Instructions:	Includes label and drawing to modify existing beam	Contact your Spider professional	Contact your Spider professional
Assembly Labels:	Order kit 700918-1 for complete label set for 700751-1*	Labeled with load ratings and counterweight chart	Labeled with load ratings and counterweight chart

*Available in rental fleet only



8-0217-4