

Safety Line (704076-1)

Spider safety line has a stronger tensile strength and quick delivery at a great price

- Firmer lay creating more control
- Smoother trailing action for trailing rope grabs
- Hockle resistant construction
- Spider-logo'd tag on all lengths
- Availability of full reels for self-sizing ropes
- Spider black and red tracer
- Conforms to and tested to OSHA 1926.502(d)(9), ANSI Z359.1-2007
- Made by Spider in the USA



704076-1	5/8 in. (16 mm) vertical lifeline	per foot
704076-600	5/8 in. (16 mm) vertical lifeline	600 ft (182.9 m)
704076-1200	5/8 in. (16 mm) vertical lifeline	1,200 ft (365.8 m)
704076-2400	5/8 in. (16 mm) vertical lifeline	2,400 ft (731.5 m)

Strength:	5,600 lb (2,540.1 kg) minimum
Weight:	10.7 lb (4.9 kg) per 100 ft (30.5 m)
Material:	5/8 in. (16 mm) diameter three strand polyester/copolymer combo

FALL
PROTECTION

MATERIAL
HOISTING

WIND ACCESS

SERVICE
EXPERTISE

FORMS,
APPLICATIONS
& DOCUMENTS

APPENDIX

OVERVIEW

TRACTION
HOISTS

DRUM HOISTS/
WORK CAGES

MODULAR
PLATFORMS

RIGGING
PRODUCTS

WIRE ROPE,
ELECTRICAL
& WELDING
ACCESSORIES

TEMPORARY
ACCESS FORMS

Call or click for more information
1-877-774-3370
www.spiderstaging.com