

Wire Rope Assemblies

Part Number -xxx denotes length i.e. 1329-175 and 4405-550	Lengths Available	Termination Rigging Point	Termination Bitter End
700939-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Tapered Brazed Bullet
701450-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Tapered Brazed Bullet
701354-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Nicropress Oval Sleeves and Galvanized Thimble	Tapered Brazed Bullet
700018-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Tapered Brazed Bullet
701478-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Tapered Brazed Bullet
1329-xxx*	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Swaged, Forged Cable Drum Hook
701990-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	18 in. Flemished Eye Splice with Steel Swaged Sleeve; Slip On Thimble	Swaged, Forged Cable Drum Hook
4405-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Swaged, Forged Cable Drum Hook
701447-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Swaged, Forged Cable Drum Hook
701353-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Nicropress Oval Sleeves and Galvanized Thimble	Swaged, Forged Cable Drum Hook
4863-xxx	200 to 750 ft (61 to 228.6 m) in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Swaged, Forged Cable Drum Hook
4775-xxx	100 to 500 ft (30.5 to 152.4 m) in 25 ft (7.6 m) increments; 550 ft (167.6 m) and above in 50 ft (15.2 m) increments	Flemish Eye Splice with Steel Swaged Sleeve and Galvanized Thimble	Swaged, Forged Cable Drum Hook

For Insulated Wire Rope Assemblies, see part numbers 701108-xxx and 701118-xxx in Wire Rope Insulation & Welding on page 135.

*1329-xxx is available with eye splice or swaged terminations. Consult your Spider professional to order the appropriate assemblies.

Construction	Min. Breaking Strength in lb (kg)	Weight/100 ft lb (kg)	Used with Traction Hoists: SC40/30, SC1000/1500, ZMAC/1000®	Used with Drum Hoists: ST-17, ST-180, ST-19 ST-26, LSR1
5/16 in. 5 x 26 WSRR XXIP Galvanized; Fiber Core	11,500 (5,216.3)	16 (7.3)	✓	
8.4 mm 5 x 26 WSR HDPP core Galvanized	11,570 (5,248)	19 (8.6)	✓	
8.4 mm 5 x 26 WSR HDPP core Galvanized 5/16 in 5 x 26 WSRR XXIP Galvanized; Fiber Core	11,570 (5,248) 11,500 (5,216.3)	19 (8.6) 16 (7.3)	✓	
8.4 mm 6 x 19 Seale XXIP IWRC	12,500 (5,669.9)	19 (8.6)	✓ PI Applications Only	
3/8 in. 6 x 19 Seale XIP IWRC	15,100 (6,849.2)	26 (11.8)	✓ PI Applications Only	
5/16 in. 5 x 26 WSRR XXIP Galvanized; Fiber Core	11,500 (5,216.3)	16 (7.3)		✓
5/16 in. 5 x 26 WSRR XXIP Galvanized; Fiber Core	11,500 (5,216.3)	16 (7.3)		✓
5/16 in. 6 x 19 EIP IWRC Galvanized	10,540 (4,780.9)	18 (8.2)		✓
8.4 mm 5 x 26 WSR HDPP core Galvanized	11,500 (5,216.3)	19 (8.6)		✓
8.4 mm 5 x 26 WSR HDPP core Galvanized 5/16 in 5 x 26 WSRR XXIP Galvanized; Fiber Core	11,570 (5,248) 11,500 (5,216.3)	19 (8.6) 16 (7.3)		✓
8.4 mm 6 x 19 Seale XXIP Preformed IWRC	12,500 (5,669.9)	19 (8.6)		✓ PI Applications Only
3/8 in. 6 x 19 Seale XIP IWRC	15,100 (6,849.2)	26 (11.8)		✓ PI Applications Only

Spider does not recommend Fist Grips for suspension wire rope terminations for general use due to manufacturer's more frequent inspection and specific torque requirements. Wire Rope Assembly specifications subject to change. Contact your Spider professional for additional information.