

# New Product Alert – Twin Turbo Retractable

## 704346-1 - SRL; TWIN TURBO



### Achieve 100% tie-off while reducing fall distance to inches

- Preferred fall arrest system when performing Mid Air Transfers, working over water or where dangling independent safety lines pose a hazard
- Requires less fall clearance because it arrests a fall within inches
- Replacement for Y-Lanyards
- Connects to the back D-ring of any fall protection harness
- Permits retractables to swivel in multiple directions for greater mobility
- Webbing pays out smoothly - extends/retracts without interruption
- Similar weight to standard Y-lanyards



**Webbing:**  
**Tensile Strength:** Min. 5,000 lbs  
**Working Length Capacity:** 6 ft  
**Technical:**  
**Max Worker Rating** 400 lbs  
**Certification:**  
**Meets the following at time of shipment:**  
**ANSI: Z359.1-2007, A10.32**  
**OSHA: 1926.502, 1910.66**  
**CSA: Z259.12-01 Class 1, Z59.2.2-98**



Part Number	Description	End Connector	Weight
704346-1	SRL; TWIN TURBO; ANSI SNAP	ANSI Snap Hook	4.9 lbs
704346-2	SRL; TWIN TURBO; ANSI REBAR	ANSI Rebar Hook	6.7 lbs
704346-3	SRL; TWIN TURBO; SNAP	Snap Hook	4.7 lbs
704346-4	SRL; TWIN TURBO; REBAR	Rebar Hook	6.1 lbs
704346-5	SRL; TWIN TURBO; SNAP; ALUM	Aluminum Snap Hook	4.2 lbs
704346-6	SRL; TWIN TURBO; REBAR; ALUM	Aluminum Rebar Hook	5.6 lbs

**Call Spider today to discuss your safety needs: (877) 774-3370**

