
Bolt Down Socket-Pedestal (foam filled) 723657



Description


Pedestals are used to elevate the davit from the base roof equipment. Heights will depend on connection, roof structure, and parapet wall height. This configuration includes a socket.

Bolt Down: Used in conjunction with embed or thru-bolt plates. **Compatible with NYSDOL Advisory Standard 101



Part Number Example:

723657-1-12-15: Foam filled, 1000 lb rated, 12" high bolt down socket-pedestal, top plate rotated at 15°



723657-1-12-15 shown above

Torque as required by project specifications.

Part Number

Moment Rating


Compatible with


Compliance

Dimensions


Material

Function





	Тор	Plate	Cloc	kwise	Rotations
--	-----	-------	------	-------	------------------



*If compliance to NYSDOL is not required, consider non-foam filled Socket-Pedestal (723667)

Spider[®] is a division of SafeWorks, LLC. This data sheet and all reproductions are the property of SafeWorks, LLC including all information contained herein and any information derived from this data sheet. Users are solely responsible for the safe and proper use of all products or any derivative products. This data sheet is only intended for illustrative purposes and should not be relied upon in place of an operating manual or a competent user trained to properly use the products depicted. All dimensions and figures shown are for general information only and should be confirmed and permission obtained from SafeWorks LLC before being used for design or construction purposes. All information is subject to change without notice. SafeWorks LLC disclaims all liability from any use or misuse of the information contained herein.

723657

Elevate davit to concrete roof connection via embed or thru-bolt

127,500 in-lb Length and Width: 17"

Height (H): 8 - 26" in 1" increments *Contact Spider for non-standard height options Plates: ASTM A572 Steel GR50, ASTM A36 Steel, and A53 Steel Pipe: ASTM A53 Grade B

Hot Dipped Galvanized (ASTM A123) Hardware: Stainless Steel ASTM F594 GR Nuts 1-8 UNC 723583-1 Embed Bolt Assembly

723733-1 Thru Bolt Assembly Welding by AWS certified welders to AWS standards. Conforms with OSHA 1910.66, CAL/OSHA title 8,

ASME A120.1-2014.

*Conforms with NYSDOL Advisory Standard 101.

Spider[®] | 365 Upland Drive, Seattle, WA 98188 | P: 855-457-8513 | F: (206) 575-6240 productsupport@spiderstaging.com | www.SpiderStaging.com