

Product Update SER 16-004

Proper use of a Hoist with a two Parted Primary Suspension Line February 03, 2016

COMPLANCE CATEGORY Safety Safety Safety Compliance is mandated within a specific operating time. Compliance Required dentifies the need for action to correct a condition that, if left uncorrected, may result in reduced equipment reliability or efficiency. Compliance may be required within a specific operating time. Compliance Required dentifies the need for action to correct a condition that, if left uncorrected, may result in reduced equipment reliability or efficiency. Compliance may be required within a specific operating time. Compliance may be predicted to some, but not necessarily all. Accomplishment at customers discretion. Customer communication, no action required. Solution of the complishment at customers discretion. PRODUCT MODELS AFFECTED Solution of the complishment and customers discretion. PRODUCT MODELS AFFECTED Solution of the complishment of the c	PURPOSE													
COMPLIANCE CATEGORY Safety Safety Safety Failure to comply with this product update could result in personal injury. Compliance is mandated within a specific operating time. Compliance Required identifies the need for action to correct a condition that, if left uncorrected, may result in reduced equipment reliability or efficiency. Compliance may be required within a specific operating time. Optional operating time. Optional identifies changes that may be beneficial to some, but not necessarily all. Accomplishment at customers discretion. Notification Customer communication, no action required. Optional / Notification Customer communication, no action required. Optional / Notification Sci000/1500 Sci30 Sci30 Sci40 Zmac Astro Sti-17 Sti-19 Sti-26 Sti-180 Platform Accessories Rafey TaP Other: Hoist Accessories Platform Accessories Rafey TaP Other: Sci000/1500 Microscories Platform Accessories Safety Accessories COMPONENT SYSTEM Electrical Mechanical Safety Other: SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use														
Safety Failure to comply with this product update could result in personal injury. Compliance is mandated within a specific operating time. Compliance Required Identifies the need for action to correct a condition that, if left uncorrected, may result in reduced equipment reliability or efficiency. Compliance may be required within a specific operating time. Optional Identifies changes that may be beneficial to some, but not necessarily all. Accomplishment at customers discretion. Notification Notification Sc1000/15000 Sc30 PRODUCT MODELS AFFECTED SC1000/15000 Sc30 PRODUCT MODELS AFFECTED SC1000/15000 MS C30 Protection Anchorage Platforms BAP TAP Other: SUB COMPONENT SYSTEM Electrical Mechanical Safety Components of the primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary Suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. ACCOMPANYING DOCUMENTS	Secondary Suspension Line.													
Operating time. Compliance Required Identifies the need for action to correct a condition that, if left uncorrected, may result in reduced equipment reliability or efficiency. Compliance may be required within a specific operating time. Optional Identifies changes that may be beneficial to some, but not necessarily all. Accomplishment at customers discretion. Notification Customer communication, no action required. PRODUCT MODELS AFFECTED SC1000/1500 SC30 SC40 Zmac Astro ST-17 ST-19 ST-26 ST-180 Platforms BAP TAP Other: Hoist Accessories Platform Accessories Rigging Accessories Safety Accessories COMPONENT SYSTEM Electrical Mechanical Safety Other: SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is <u>not acceptable</u> to use a single secondary suspension line through the secondary line safety brake, and it is <u>not acceptable</u> to use a single secondary suspension line through the secondary line safety brake, and it is <u>not acceptable</u> to the off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is <u>not acceptable</u> to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage <u>must be</u> independent of the platform via use of an independent lifeline or other means.	Safety Failure to comply with this product update could result in						☐ 1Prior to unit startup or prior to continued operation (Immediate							
Notification	operating time. Compliance Required Identifies the need for action to correct a condition that, if left uncorrected, may result in reduced equipment reliability or efficiency. Compliance may be required within a specific operating time.						2 At first opportunity (Prior to Next Scheduled Maintenance Interval)							
PRODUCT MODELS AFFECTED SC1000/1500 SC30 SC40 Zmac Astro ST-17 ST-19 ST-26 ST-26 ST-180 Platforms BAP TAP Other: Hoist Accessories Platform Accessories Rigging Accessories COMPONENT SYSTEM Electrical Mechanical Safety Other: SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS	Identifies changes that may be beneficial to some, but not necessarily all. Accomplishment at customers discretion. Notification						Next Scheduled Maintenance Interval 4							
SC1000/1500 SC30 SC40 Zmac Astro ST-17 ST-19 ST-26 ST-180 Platforms BAP TAP Other: Hoist Accessories Platform Accessories Rigging Accessories Safety Accessories COMPONENT SYSTEM Electrical Mechanical Safety Other: SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS	Optional / Notification													
ST-26 ST-180 Platforms BAP TAP Other: Hoist Accessories Platform Accessories Rigging Accessories Safety Accessories COMPONENT SYSTEM Electrical Mechanical Safety Other: SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS	PRODUCT MODELS AFFECTED													
Hoist Accessories Platform Accessories Rigging Accessories Safety Accessories COMPONENT SYSTEM Electrical Mechanical Safety Other: SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS	SC1000/1500 SC30] ST	-17	ST-19			
COMPONENT SYSTEM Electrical								<u> </u>						
Electrical Mechanical Safety Other: SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means.	☐ Hoist Accessories ☐ Platform Accessories ☐ Rigging Accessories ☐ Safety Accessories													
Electrical Mechanical Safety Other: SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means.	COMPONENT SYSTEM													
SUB COMPONENT Secondary Suspension Wire Rope Assembly ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS			П	/lechanical	Safety					Other:				
ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS														
ACTION REQUIRED When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS														
When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS	Secondary Suspension Wire Rope Assembly													
When two parting the hoist primary suspension line to double the lifting capacity of the hoist, it is not acceptable to use a single secondary suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS	ACTION PROLUPED													
secondary suspension line through the secondary line safety brake, and it is not acceptable to tie off to the platform for Personal Fall Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS		hoist prima	arv su	spension line to de	ouble the	lifting can	acit	v of the hoist it	t is r	not :	acceptable to	use a single		
Protection Anchorage. This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS														
This setup results in a case where if the primary suspension line were to fail on the hoist and you have a 1500 lb hoist lifting 3000 lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS	· · · · · · · · · · · · · · · · · · ·													
lbs, the secondary suspension line and hoist safety would be trying to arrest a load which the safety was not designed. The impact forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is not acceptable to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage must be independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS														
forces this could pose may be above the termination strength of the wire rope depending on the construction. Therefore it is <u>not acceptable</u> to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage <u>must be</u> independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS														
Therefore it is <u>not acceptable</u> to use a hoist equipped with a secondary suspension line when two parting the primary suspension line. Personal Fall Protection Anchorage <u>must be</u> independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS														
line. Personal Fall Protection Anchorage <u>must be</u> independent of the platform via use of an independent lifeline or other means. ACCOMPANYING DOCUMENTS	11.000 timo oodid pose													
ACCOMPANYING DOCUMENTS														
	line. Personal Fall Pro	otection Ancl	horag	e <u>must be</u> indepe	ndent of	the platfor	m v	ia use of an ind	epe	nde	ent lifeline or	other means.		
NONE	ACCOMPANYING DO	CUMENTS												
	NONE													